



Taylex[®]
Tanks

Manufacturing Tanks Since 1969

Wastewater & Rainwater Specialists

TAYLEX INDUSTRIES

Taylex Industries Pty Ltd
A.B.N. 35 113 453 091

Postal Address:
56 Prairie Road
Ormeau Queensland 4208

Phone: 07 3441 5200
Fax: 07 3287 4199

Non-Trafficable Lids for tanks means

A non-trafficable lid has a total load limit of 300kgs. These lids may NOT be buried under any circumstance. You may NOT build any structures over these tanks i.e. Decks that use the tank as support, hot tubs, outdoor entertainment areas, etc.

In most cases non-trafficable tanks that are buried should protrude approximately 300mm from the ground to the top of the lid.

Under NO CIRCUMSTANCE may you drive over, or place the tank in a position that it can be driven over by you or any future owners of the property.

Under NO CIRCUMSTANCE may you cover these tanks with soil, bark or any other material.

Please refer to the Rainwater Tank Excavation/Installation Instructions if you require more information.

Light-Trafficable Lids for tanks means

Taylex Industries makes a range of light-trafficable lids that are engineered design. They have a load capacity from 2 tonnes to 8 tonnes.

In most cases these tanks have a design loading of 2 tonnes. This means the maximum design load is 3kpa or 2.0 tonne static.

It is imperative that when putting a load on the lid that it does not exceed the engineers specifications. (Please see Engineering Design for each tank to select which tank will suit your purpose.)

The Taylex range of underground tanks can be used for a wide range of purposes, and are installed in many different ways. Please ensure that the end use of the tank does not exceed the top loading weight of the Engineered Specification.

Please refer to the Rainwater Tank Excavation/Installation Instructions if you require more information.

Taylex Industries takes no responsibility for any damage that occurs due to incorrect use of its precast concrete tank range.

**T
A
Y
L
E
X

I
N
D
U
S
T
R
I
E
S**